#### Storage Tanks for Helium Gas in B902

- The storage tanks for helium gas in B902 consists for clean and dirty (not pure sufficiently for liquefaction) helium.
- In addition there are a few buffer tanks for cryogenic operation.
- There are 4 groups of tanks used for clean storage.
- There are 2 groups of tanks used for dirty storage.
- Photo of the gas storage tanks and associated relief valves are given later in this file.
- Dimension and storage capacity are given next.

1

#### Storage Tanks for Clean Helium

• There are 4 groups of tanks for clean storage as show below.

	Dia.	Wall	Length	Vol
	in	in	ft	CF
Clean Storage		(est).	(est)	
Clean tank 1	84	0.6	45	1604
Clean tank 2	96	0.6	45	2005
Tube B #1	24	0.25	80	241
Tube B #2	50	0.5	45	589

#### Total Storage Capacity for Clean Helium

Tank	No.	Volume	Volume	
		each	subtotal	
		CF	CF	
Clean	4	2005	8021	
	1	1604	1604	
Tube B #1	33	241	7952	
Tube B #2	4	589	2357	
Total			19935	

At 225 psia pressure, these tanks are capable of storing  $\sim$  300,000 standard cubic foot of helium (equivalent to 6 x 50,000 cubic foot trailers or  $\sim$  11,000 L of liquid helium).

As June 7 2010, there is a plan to return one 2000 cubic foot tank to NSLS for the X17 cryogenic system. When that tank is removed, the total capacity will be reduced by  $\sim 10\%$ .

#### Storage Tanks for Dirty (Contaminated) He

- There are 2 groups of tanks for contaminated helium with 24" and 66" dia.
- These tanks are designed for 500 psi and are capable of storing ~ 90,00 SCF of helium.

	No.	Dia.	Wall	Length	Vol	Vol.	Pressure	Vol.
		in	in	ft	CF	CF	At	SCF
Dirty Storag	ge		(est).	(est)		Sub-total	psia	Sub-total
Tube #3	6	24	0.25	40	120	723	500	24096
Tube #4	2	66	1	45	1005	2011	500	67021
Total						2734		91117

### Photo of Storage Tanks

5

# 3 HP Clean He Storage Tanks Tank 1 – the smallest



### B902 Old HP Helium Storage (Left)



Upper 6 cylinders are for dirty storage and bottom 4 cylinders are for clean gas. These 4 clean storages have one Circle Seal relief valve, 5159 B-8-1500 J relief Valve. Flange for the 4 clean storages are 1500 lb standard, ASA B16.5, 1961. (O.D. 23",  $12 \cdot 1-7/8$ " bolts,  $\sim 5$ " thick > 4-1/4")

### B902 Old HP Helium Storage (Middle)



These two tanks are for dirty helium gas storage. One Circle Seal relief valve, K 5159 13-4MP-600, is shared by these two tanks and the 6 upper cylinders in the left of tank farm.

### Plate - B902 Old HP Helium Storage (Middle)



A plate stating 2800 psi MAWP and manufactured in 7/15/60.

ç

### B902 Old HP Helium Storage (Right)



These 33 cylinders are for clean helium gas storage. Rated 600 psi, typically operating at 190 psi. One relief valve is installed for each 3 cylinders. Circle Seal 5159B, 2MP-300, Relief Valve. Range: 286 – 345 psi.

#### Relief Valve - B902 Old HP Helium Storage (Right)





These 33 cylinders are for clean helium gas storage. Rated 600 psi, typically operating at 190 psi. One relief valve is installed for each 3 cylinders. 11 Circle Seal 5159B, 2MP-300, Relief Valve. Range: 286 – 345 psi.

#### 3 HP He Storage Tanks Tank 1 – the smallest



# HP He Storage Tank 1 – Relief Valve set at 240 psig, 1054 SCFM



13

## Relief Valve - B902 Helium Storage (Tank 2 – 5?)





# Relief Valve - B902 Helium Storage (Tank 2 – 5?)





15

### LP He Storage - Buffer Tank



# Relief Valve - B902 Helium Storage (Tank 6)



17

### LP He Storage (Red Tank)



### LP He Storage (Red Tank) – Relief V.



# Relief Valve and Rupture Disc at Inlet to B902 Warm Storage (Tank 8)








### 3 HP He Storage Tanks Tank 1 – the smallest

21

## HP He Storage Tank 1 – ASME Plate MAWP – 275 psig



#### HP He Storage Tank 1 – ASME Plate



23

### HP He Storage Tank 2 – ASME Plate




#### HP He Storage Tank 3? – ASME Plate



25

# LP He Storage (Buffer Tank?) ASME Plate



### LP He Storage (Red Tank) – BNL Label

